

구리 버스바 허용 전류표

두께 (mm)	폭 (mm)	단면적 (Square)	1장		2장		3장	
			DC	AC	DC	AC	DC	AC
3	20	60	225	225				
	25	75	275	275				
	30	90	320	320				
	50	150	430	425				
4	30	120	380	375				
	40	160	485	480				
5	30	150	430	425				
	40	200	550	520				
	50	250	660	650				
	60	300	780	760				
	75	375	950	930	1920	1790		
6	30	180	480	470	1920			
	40	240	610	600				
	50	300	730	720				
	60	360	860	840				
	75	450	1050	1010	2090	1910		
	80	480	1110	1070	2190	2000		
	100	600	1350	1280	2620	3330	3670	3060
8	30	240	570	560				
	40	320	720	700				
	50	400	860	840				
	60	480	1010	970				
	75	600	1220	1160	2390	2120		
	80	640	1290	1220	2150	2210		
	100	800	1530	1470	2290	2560		
10	40	400	830	800	1730	1600		
	50	500	990	950	2010	1810		
	60	600	1150	1090	2280	2010		
	75	750	1390	1290	2680	2290		
	80	800	1460	1360	2810	2380		
	100	1000	1780	1620	3310	2730	4750	3490
	120	1200	1970	1850	3770	3000	5480	3800
	150	1500	2550	2260	4550	3590	6440	4450
15	50	750	1200	1120				
	75	1125	1650	1480				
	100	1500	2100	1830				
	150	2250	3100	2640				

